

CGH35015F

15 W, 3300-3900 MHz, 28V, GaN HEMT for WiMAX

Cree's CGH35015F is a gallium nitride (GaN) high electron mobility transistor designed specifically for 802.16-2004 WiMAX Fixed Access applications. GaN HEMTs offer high efficiency, high gain and wide bandwidth capabilities, which makes the CGH35015F ideal for 3.3-3.9GHz WiMAX and BWA amplifier applications. The transistor is available in a flange package.



Package Type: 440166
PN: CGH35015F

Typical Performance 3.4-3.9GHz ($T_c = 25^\circ\text{C}$)

Parameter	3.4 GHz	3.5 GHz	3.6 GHz	3.8 GHz	3.9 GHz	Units
Gain @ $P_{OUT} = 2\text{ W}$	11.6	11.8	12.0	11.8	11.2	dB
P_{OUT} @ 2.0 % EVM	33.0	33.0	33.0	33.5	33.5	dBm
Drain Efficiency @ 2.0 % EVM	23.0	23.0	24.0	18.0	17.0	%
Input Return Loss	4.0	4.5	6.0	13.0	9.0	dB

Note:

Measured in the CGH35015F-TB amplifier circuit, under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, 5 ms Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3.

Features

- 3.3 - 3.9 GHz Operation
- >11 dB Small Signal Gain
- >2.0 W P_{OUT} at 2.0 % EVM
- 24 % Efficiency at 2.0 W P_{OUT}
- 15 W Typical P_{3dB}
- WiMAX Fixed Access 802.16-2004 OFDM





Absolute Maximum Ratings (not simultaneous) at 25 °C Case Temperature

Parameter	Symbol	Rating	Units
Drain-Source Voltage	V_{DSS}	84	Volts
Gate-to-Source Voltage	V_{GS}	-10, +2	Volts
Storage Temperature	T_{STG}	-55, +150	°C
Operating Junction Temperature	T_J	175	°C
Thermal Resistance, Junction to Case ¹	$R_{\theta JC}$	5.0	°C/W

Note:

¹ Measured for the CGH35015F at $P_{DISS} = 14W$.

Electrical Characteristics ($T_c = 25^\circ C$)

Characteristics	Symbol	Min.	Typ.	Max.	Units	Conditions
DC Characteristics						
Gate Threshold Voltage	$V_{GS(th)}$	-3.0	-2.5	-1.8	VDC	$V_{DS} = 10 V, I_D = 3.6 mA$
Gate Quiescent Voltage	$V_{GS(Q)}$	-	-2.4	-	VDC	$V_{DS} = 28 V, I_D = 60 mA$
Saturated Drain Current	I_{DS}	2.4	2.7	-	A	$V_{DS} = 6.0 V, V_{GS} = 2.0 V$
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	84	100	-	VDC	$V_{GS} = -8 V, I_D = 3.6 mA$
Case Operating Temperature	T_c	-10	-	+105	°C	
Screw Torque	T	-	-	60	in-oz	Reference 440166 Package Revision 3
RF Characteristics^{2,3} ($T_c = 25^\circ C, F_0 = 3.5 GHz$ unless otherwise noted)						
Small Signal Gain	G_{SS}	11	12	-	dB	$V_{DD} = 28 V, I_{DQ} = 60 mA$
Drain Efficiency ¹	η	22	24	-	%	$V_{DD} = 28 V, I_{DQ} = 60 mA, P_{AVE} = 2.0 W$
Back-Off Error Vector Magnitude	EVM_1	-	2.5	-	%	$V_{DD} = 28 V, I_{DQ} = 60 mA, P_{AVE} = 18 dBm$
Error Vector Magnitude	EVM_2	-	2.0	-	%	$V_{DD} = 28 V, I_{DQ} = 60 mA, P_{AVE} = 2.0 W$
Output Mismatch Stress	VSWR	-	10 : 1	-	Ψ	No damage at all phase angles, $V_{DD} = 28 V, I_{DQ} = 60 mA,$ $P_{AVE} = 2.0 W$
Dynamic Characteristics						
Input Capacitance	C_{GS}	-	5.00	-	pF	$V_{DS} = 28 V, V_{GS} = -8 V, f = 1 MHz$
Output Capacitance	C_{DS}	-	1.32	-	pF	$V_{DS} = 28 V, V_{GS} = -8 V, f = 1 MHz$
Feedback Capacitance	C_{GD}	-	0.43	-	pF	$V_{DS} = 28 V, V_{GS} = -8 V, f = 1 MHz$

Notes:


¹ Drain Efficiency = P_{OUT} / P_{DC}

² Under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, 5 ms Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3.

³ Measured in the CGH35015F-TB test fixture.


Typical WiMAX Performance

Modeled vs Measured Performance of CGH35015F in Broadband Amplifier Circuit
 $V_{DD} = 28\text{ V}$, $I_{DQ} = 60\text{ mA}$, OFDM BW = 3.5 MHz




Single Tone CW Gain and Efficiency of CGH35015F vs. Output Power in Broadband Amplifier Circuit

$V_{DD} = 28\text{ V}$, $I_{DQ} = 60\text{ mA}$, Freq = 3.6 GHz




Typical WiMAX Performance

Typical EVM and Efficiency of CGH35015F in Broadband Amplifier Circuit at 3.6 GHz F=3.6 GHz, 802.16-2004 OFDM, P/A=9.8 dB



Note:
Under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3.


Typical Constellation Chart, Spectral Mask, and EVM of CGH35015F in Broadband Amplifier Circuit at 3.6 GHz $V_{DD} = 28 V, I_{DQ} = 60 mA, P_{AVE} = 2.0 W$





Typical WiMAX Performance


Typical EVM and Efficiency at 22dBm and 33 dBm vs Frequency of CGH35015F in Broadband Amplifier Circuit




Note:

Under 802.16 OFDM, 3.5 MHz Channel BW, 1/4 Cyclic Prefix, 64 QAM Modulated Burst, Symbol Length of 59, Coding Type RS-CC, Coding Rate Type 2/3.


CGH35015F-TB Demonstration Amplifier Circuit



CGH35015F-TB Demonstration Amplifier Circuit Outline




CGH35015F-TB Demonstration Amplifier Circuit Schematic



CGH35015F-TB Demonstration Amplifier Circuit Bill of Materials

Designator	Description	Qty
C1	CAP, 0.7pF, +/-0.1 pF, 0603, ATC 600S	1
C2	CAP, 0.8pF, +/-0.1 pF, 0603, ATC 600S	1
C10,C11	CAP, 2.4pF,+/-0.1pF, 0603, ATC 600S	2
C4	CAP, 10.0pF, +/-5%, 0603, ATC 600S	1
C5,C13	CAP, 39 PF±5%, 0603, ATC 600S	2
C14	CAP, 100 PF±5%, 0603, ATC 600S	1
C6	CAP, 470 PF ±10%,100 V, 0603	1
C7,C15	CAP, 33000PF, 100V, 0805, X7R	2
C8	CAP, 10UF, 16V, SMT, TANTALUM (240096)	1
C16	CAP, 1.0UF ±10%, 100V, 1210, X7R	1
C17	CAP, 33UF, 100V, ELECT, FK, SMD	1
R1,R2	RES, 1/16W, 0603, 0 Ohms, 1%	2
R3	RES, 1/16W, 0603, 47 Ohms ≤5%	1
R4	RES, 1/16W, 0603, 100 Ohms ≤5%	1
J1	5-PIN, MOLEX, MALE, CONNECTOR	1
J2	2-PIN, MOLEX, MALE, CONNECTOR	1
J3,J4	SMA, FEMALE, CONNECTOR	2
Q1	CGH35015	1

Product Dimensions CGH35015F (Package Type — 440166)



- NOTES:
1. DIMENSIONING AND TOLERANCING PER ANSI Y14.5M, 1982.
 2. CONTROLLING DIMENSION: INCH.
 3. ADHESIVE FROM LID MAY EXTEND A MAXIMUM OF 0.020" BEYOND EDGE OF LID.
 4. LID MAY BE MISALIGNED TO THE BODY OF THE PACKAGE BY A MAXIMUM OF 0.008" IN ANY DIRECTION.
 5. ALL PLATED SURFACES ARE Ni/AU

DIM	INCHES		MILLIMETERS	
	MIN	MAX	MIN	MAX
A	0.155	0.165	3.94	4.19
B	0.004	0.006	0.10	0.15
C	0.115	0.135	2.92	3.43
D	0.057	0.067	1.45	1.70
E	0.195	0.205	4.95	5.21
F	0.045	0.055	1.14	1.40
G	0.545	0.555	13.84	14.09
H	0.280	0.360	7.87	8.38
J	Ø .100		2.54	
K	0.375		9.53	

- PIN 1. GATE
 PIN 2. DRAIN
 PIN 3. SOURCE



Disclaimer

Specifications are subject to change without notice. Cree, Inc. believes the information contained within this data sheet to be accurate and reliable. However, no responsibility is assumed by Cree for any infringement of patents or other rights of third parties which may result from its use. No license is granted by implication or otherwise under any patent or patent rights of Cree. Cree makes no warranty, representation or guarantee regarding the suitability of its products for any particular purpose. "Typical" parameters are the average values expected by Cree in large quantities and are provided for information purposes only. These values can and do vary in different applications and actual performance can vary over time. All operating parameters should be validated by customer's technical experts for each application. Cree products are not designed, intended or authorized for use as components in applications intended for surgical implant into the body or to support or sustain life, in applications in which the failure of the Cree product could result in personal injury or death or in applications for planning, construction, maintenance or direct operation of a nuclear facility.

For more information, please contact:

Cree, Inc.
4600 Silicon Drive
Durham, NC 27703
www.cree.com/wireless

Ryan Baker
Marketing
Cree, Wireless Devices
919.287.7816

Tom Dekker
Sales Director
Cree, Wireless Devices
919.313.5639